

# DIGITAL PRESSURE INDICATOR

## MODEL AI-PRI



### SPECIFICATIONS

Pressure Measuring Range	0 to 1, 2,4, 6, 10, 25, 40, 100, 200, 250 upto 5000 Bar 0to 100, 200,500, 1000, 2000,3000, 5000, 9999 mm.WC. (Optional Units of PSI, mm. Hg., In. Hg.also available)
Display	4 Digit Red L.E.D. Display
Resolution	1/0.1/0.001 PV ( 1mm.W.C.)
Power	Instrument : 230 Volts A.C. , Single Phase Transmitter : 24 V.D.C. ( Provided in Instrument )
Accuracy	+/- 0.25% of Full Scale.
Size	Instrument Enclosure is in 96x96 mm. (Lx B) Transmitter is with ¼” Male Threaded End
Construction	Instrument is in panel mounting Type ABS Plastic BodyTransmitter is in Stainless Steel Body with S.S. 316 Wetted Parts
Transmitter Output	4-20 mA , 2 wire to instrument
Weight	Approx. 1 Kg. for the Set of Instrument & Transmitter
Optional Extra	4 – 20 mA Retransmission Output from Indicator , Relay Output at User Set Point ( At Extra Price )

Temp | Humidity | Pressure | Differential Pressure | Vacuum | Gases | Particle | Air Flow  
Moisture | Dissolved Oxygen | Radiation | Air Quality | Light / Lux | Distance | Vibration

### Instrukart

Ph : +91 (40)40262020 | Mob : +91 88865 50506;  
Email : info@instrukart.com | www.instrukart.com  
Head Office: #18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.

