

Sentek SD119-G Smoke Detector



Features:

- Wide voltage range, and stable yield
- Advanced location and segregation calculations
- Easy establishment and support
- Sleek low-profile lodging outline
- Durable sensor head, no requirement for substitution
- SMD circuit board outline palatable quality and dependability ensured
- Integrated warm identifier for SD119-2H and SD119-4H models
- N/C (typical/close)- N/O (ordinary/open)selectable hand-off yield

Specifications:

Manufacturer	: Sentek
Model No	: SD 119-G
Measuring Parameters	: Humidity, Temperature
Temperature	: -10°C to 50°C
Humidity	: 0 to 95% RH, no condensation or icing
Operating Temperature	: -20°C to 80°C
Storage Temperature	: -30°C to 80°C
Ceiling Spacing	: 50 foot rating for heat sensor
Reset Voltage	: less than 5 volt
Remote Output	: 3.0 to 3.7V DC when in series a LED & Ω resistor
Reset Time	: less than 1 second
Alarm Indicator	: LED continuously emitting red light
Dimensions	: 100 X 46 mm with base
Weight	: 130 Grams



Clean Rooms | Pharma | Hospital | HVAC | BulkDrugs | Chemicals | Heavy Machinery | Hydraulics | Vacuum Industry
Green House | Server Room | Confined Space | Cold Storage

Instrukart Holdings

India Toll Free : 18000-121-0506 | Ph : +91 (40)40262020

Mob +91 7331110506 | Email : info@instrukart.com

#18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.

