



## EASY LOG

### Features:

- Memory for 32,700 readings
- LCD to show logging information easily
- Free selectable measurement cycle from 1sec to 24hrs.
- Battery life: more than 3 years (Under Ideal condition at 22°C)
- Display all status for Alarm and Record through 2 LED's.
- Alarm display if user-defined max/min values are exceeded
- Analysis software used to view graphically or Text mode For logging data.
- USB Computer Interface (Advanced Software Program for all windows)
- Power 3.6V ER 14250 X 1

### Technical Data :

Basic Functions	RH		Temp.			
Measuring Range	0~100%RH		-40°C~70°C		-40°F~158°F	
Accuracy	0~35% & 80~100% RH	<±5% RH	-40°C~40°C	±1.0 °C	-40°F~104°F	±1.8 °F
	35%~80% RH	±3.0% RH	40°C~70°C	±2.0 °C	104°F~158°F	±3.6 °F
Resolution	0.1%RH		0.1°C			
Memory	32,000 (16,000 each for Temperature & Humidity)					
Measuring Rate	1sec. to 24hrs					
Response Time	< 30 S					

- Standard Accessories : Hard Carrying Case, Safety Lock USB Cable & Software
- Dimensions : 94.8(H) x 51.4(W) x 29.5(D)mm

Clean Rooms | Pharma | Hospital | HVAC | BulkDrugs | Chemicals | Heavy Machinery | Hydraulics | Vacuum Industry  
Green House | Server Room | Confined Space | Cold Storage

## Instrukart Holdings

India Toll Free : 1800-121-0506 | Ph : +91 (40)40262020

Mob +91 7331110506 | Email : info@instrukart.com

#18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.

