



101B+



108B+TRMS



Pocket Size

<p>Auto Ranging, 3½ Digits 4000 Counts LCD with Backlight, APO, Capacitance, REL Δ Frequency, Duty Cycle</p> <p>Ranges</p> <p>DC Voltage 400mV / 4 / 40 / 400 / 1000V</p> <p>Accuracy ± (0.5% rdg + 4 dgt) on 400mV / 4 / 40 / 400V ± (0.8% rdg + 4 dgt) on 1000V</p> <p>AC Voltage 4 / 40 / 400 / 750V</p> <p>Accuracy ± (1.2% rdg + 4 dgt) on all ranges except ± (1.5% rdg+4 dgt) on 750V</p> <p>AC Response 40Hz ~ 400Hz</p> <p>DC Current 40 / 400mA / 4 / 10A</p> <p>Accuracy ± (1.0% rdg + 4 dgt) on 40 / 400mA ± (1.5% rdg + 4 dgt) on 4 / 10A</p> <p>AC Current 40 / 400mA / 4 / 10A</p> <p>Accuracy ± (2.0% rdg + 4 dgt)</p> <p>AC Response 40Hz ~ 200Hz</p> <p>Resistance 400Ω / 4 / 40 / 400KΩ / 4 / 40MΩ</p> <p>Accuracy ± (0.8% rdg + 4 dgt) on all ranges except ± (2.0% rdg + 4 dgt) on 40MΩ</p> <p>Capacitance 4.000 / 40.00 / 400.0nF / 4.000 / 40.00 / 200.0μF</p> <p>Accuracy ± (3.5% rdg + 4 dgt) on all ranges except ± (2.5% rdg + 4 dgt) on 40.00nF ± (5.0% rdg + 4 dgt) on 4.000nF</p> <p>Frequency 99.99Hz ~ 10.00MHz</p> <p>Sensitivity 1V to 36V AC</p> <p>Accuracy ±(0.08% rdg + 2 dgt)</p>	<p>TRMS, Auto Ranging, 3½ Digits 6000 Counts LCD with Backlight, APO, Capacitance, Frequency, Duty Cycle, Temperature</p> <p>Ranges</p> <p>DC Voltage 60 / 600mV / 6 / 60 / 600 / 1000V</p> <p>Accuracy ± (1.0% rdg + 10 dgt) on 60 / 600mV ± (0.5% rdg + 3 dgt) on 6 / 60 / 600 / 1000V</p> <p>AC Voltage^{TRMS} 60 / 600mV / 6 / 60 / 600 / 750V</p> <p>Accuracy ± (1.0% rdg + 3 dgt) on all ranges except ± (3.0% rdg + 3 dgt) on 60 / 600mV</p> <p>AC Response 1Hz ~ 1KHz</p> <p>DC Current 60 / 600mA / 6 / 10A</p> <p>Accuracy ± (1.5% rdg+3 dgt)</p> <p>AC Current^{TRMS} 60 / 600mA / 6 / 10A</p> <p>Accuracy ± (1.5% rdg + 3 dgt)</p> <p>AC Response 1Hz ~ 1KHz</p> <p>Resistance 600Ω / 6 / 60 / 600KΩ / 6 / 60MΩ</p>	<p>Accuracy ± (0.5% rdg + 3 dgt) on 600Ω ± (0.5% rdg + 2 dgt) on 6 / 60 / 600kΩ / 6MΩ ± (1.5% rdg + 3 dgt) on 60MΩ</p> <p>Capacitance 9.999 / 99.99 / 999.9nF / 9.999 / 99.99 / 999.9μF / 9.999mF</p> <p>Accuracy ± (2.0% rdg + 5 dgt) on all ranges except ± (5.0% rdg + 5 dgt) on 9.999mF ± (5.0% rdg + 20 dgt) on 9.999nF</p> <p>Frequency 99.99Hz ~ 10.00MHz</p> <p>Accuracy ±(0.08% rdg + 2 dgt)</p> <p>Duty Cycle 0.1% ~ 99.9%</p> <p>Accuracy ± (0.08% rdg + 2 dgt)</p> <p>Temperature -20°C ~ 1000°C / -4°F ~ 1832°F</p> <p>Accuracy ±(1.0% rdg + 5 dgt) on <400°C / <752°F ±(1.5% rdg + 15 dgt) on >400°C / >752°F</p> <p>Measuring Category CAT III 600V, CAT II 1000V</p> <p>SP Function Diode Test, Audible Continuity, Data Hold</p> <p>Power Two 1.5V 'AAA' Battery</p> <p>Low Battery 'L' is indicated</p> <p>Battery Life 200 hours typical</p> <p>Dimensions 130 x 65 x 32mm (approx.)</p> <p>Weight 130gms Including Battery (approx.)</p> <p>Accessories One Pair of Test Leads, Battery (installed), Instruction Manual & K Type Thermocouple (upto 260°C)</p>
<p>Duty Cycle 0.1% ~ 99.9%</p> <p>Sensitivity 1V to 36V AC</p> <p>Accuracy ± (0.08% rdg + 2 dgt)</p> <p>Measuring Category CAT III 600V, CAT II 1000V</p> <p>SP Function Diode Test, Audible Continuity, Data Hold</p> <p>Power Two 1.5V 'AAA' Battery</p> <p>Low Battery 'L' is indicated</p> <p>Battery Life 200 hours typical</p> <p>Dimensions 130 x 65 x 32mm (approx.)</p> <p>Weight 130gms Including Battery (approx.)</p> <p>Accessories One Pair of Test Leads, Battery (installed) & Instruction Manual</p>		

Clean Rooms | Pharma | Hospital | HVAC | BulkDrugs | Chemicals | Heavy Machinery
 Hydraulics & Vacuum Industry | Green House | Server Room | Confined Space | Cold Storage

Instrukart Holdings

India Toll Free : 1800-121-0506 | Ph : +91 (40)40262020

Mob +91 7331110506 | Email : info@instrukart.com

#18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.