

The WatchGas QGM is a versatile multi-gas monitor engineered to keep you and your staff safe while working in hazardous environments. The WatchGas QGM offers detection for up to four different gases.

The WatchGas QGM monitors oxygen, hydrogen sulfide, carbon monoxide and combustible gases. When the concentrations of these gases exceed the alarm thresholds, the WatchGas QGM alerts the user by vibrating, flashing LEDs and a 90dB acoustic alarm. An integrated data- and event logger registers peak and average values, alarms, calibration dates, and bump test information for up to two months. All logs can be downloaded to your PC through the WatchGas IR-link software.

The QGM is available as a 2-, 3- or 4-gas monitor.

A catalytic LEL sensor comes as standard. Alternatively, you can specify your QGM with a Non-Dispersive Infrared Sensor. The IR LEL sensor consumes less energy, enhancing the battery life to up to two months on a single charge.

The IR LEL sensor has a few other advantages as well. It can measure combustible gases in the absence of oxygen, making it more useful in environments where oxygen levels may vary. Furthermore, it is less susceptible to poisoning by silicone and sulfur.



Key Features

- IECEx and ATEX zone 0 approved
- Simple single button operation
- Durable, grippy housing
- Displays actual gas concentrations, TWA and STEL values
- Adjustable alarm levels using the WatchGas IR Link
- Data log: up to two months or more
- Optical, acoustic and vibrating alarms
- Docking station available for rapid bump test and calibration

Application examples:

- (Petro)chemical plants and factories
- Tank storage parks
- Wastewater treatment facilities
- Mining industry
- Construction sites
- Governments/first responders
- Food and beverage industry

QGM-IR battery life up to two months of continuous operation

QGM-CAT battery life up to 24 hours of continuous operation

Detector specifications

Model	QGM			
	LEL	O ₂	CO	H ₂ S
Measuring type	Diffusion			
Measuring method	Catalytic [QGM-CAT] Infrared [QGM-IR]	Electrochemical		
Measuring range	0-100 %LEL	0-30 % ^{VOL}	0-500 ppm	0-100 ppm
Resolution	1 % LEL	0.1 % ^{VOL}	1 ppm	0.1 ppm
Sensor life time	> 2 year	2 year	> 2 year	> 2 year
Response time	< 15sec/90%scale	< 15sec/90%scale	< 30sec/90%scale	< 30sec/90%scale
Operation	Single Button			
Alarm Display	Digital LCD display, LCD Backlight, indicator LEDs, flashing alarm			
Operation mode display	Visual: LCD alarm display, LCD Backlight, Indicator LED Acoustic: buzzer (90 db @ 10 cm) and vibrating alarm			
Event log	Data log 2 months or more Event log / calibration log / bump log: 30 event			
Mounting type	Stainless steel belt clip			
Programming	WatchGas IR Link with PC software			
Operation temperature	-20 to +50° C			
Operating Humidity	10 to 95% RH, non-condensing			
Battery	Type: Lithium-ion rechargeable battery Charging time < 6h			
Operation time	QGM-CAT: 24 hours, QGM-IR: 2 months			
Housing	Rugged durable housing with impact proof coating IP67			
Dimensions	60 x 40 x 118 mm (WxDxH)			
Weight	< 240 g			
Approval	QGM-IR: Class I, Division 1, Groups A,B,C, and/or D, T4 Ex ia IIC T4 Ga Class 1, Zone 0, AEx ia IIC T4 Ga Sira 18ATEX2059X Inmetro: Ex ia IIC T4 Ga EAN-13: 8719992974877 (LEL/O ₂ /CO/h ₂ S) EAN-13: 8719992974894 (LEL/O ₂) EAN-13: 8719992974900 (LEL)		QGM-CAT: Class I, Division 1, Groups A,B,C, and/or D, T4 Ex da ia IIC T4 Ga Class 1, Zone 0, AEx da ia T4 Ga Sira 18ATEX2059X Inmetro: Ex da ia IIC T4 Ga EAN-13: 8719992974917 (LEL/O ₂ /CO/h ₂ S) EAN-13: 8719992974724 (LEL/O ₂) EAN-13: 8719992974931 (LEL)	
Option	WatchGas IR Link, WatchGas Docking Station			

Clean Rooms | Pharma | Hospital | HVAC | BulkDrugs | Chemicals | Heavy Machinery | Hydraulics | Vacuum Industry
Green House | Server Room | Confined Space | Cold Storage

Instrukart Holdings

India Toll Free : 1800 -121-0506 | Ph : +91 (40)40262020

Mob +91 7331110506 | Email : info@instrukart.com

#18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.