

Tester

Hioki 3287

Hioki 3287 Hi Tester is a compact and portable device that is easy to use and features a large, easy-to-read LCD display. This Hioki Hi Tester also features a variety of useful functions such as data hold function, rotating dial for easy operation making it a highly efficient and user-friendly device.

Applications: *Electrical Maintenance and Troubleshooting, Power Quality Analysis, Energy Auditing, Electrical Safety, Industrial Automation.*

Hioki 3287 Hi Tester is a portable device used to measure the AC/DC current and voltage clamp meter that measures the continuity and resistance. This Hioki Clamp Meter also features a double jaw lever and slim design to access the crowded wires

Feature of Hioki Digital Clamp Meter

- Easy and compact design
- LCD display with a good amount of brightness
- 1 year manufacturing warranty



Manufacturer	Hioki
Model No	3287
DC Current	10.00/ 100.0 A
Accuracy	±1.5 %
AC Current	10.00/ 100.0 A (10 Hz to 1 kHz, True RMS)
Accuracy	±1.5 %
DC Voltage	419.9 mV to 600 V, 5 ranges
Accuracy	±1.3 %
AC Voltage	4.199 V to 600 V, 4 ranges (30 to 500 Hz, True RMS)
Accuracy	±2.3 %
Resistance	419.9 Ω to 41.99 MΩ, 6 ranges
Accuracy	±2 %
Crest factor	2.5 or less (150 A, 1000 V max.)
Display	LCD, max. 4199 dgt., Display refresh rate: 2.5 times/s
Power Supply	Coin type lithium battery (CR2032) ×1, Continuous use 25 hours
Supply Scope	Coin type lithium battery (CR2032) × 1, Carrying case 9398 ×1, Test lead L9208 ×1, Instruction manual ×1
Dimension	57 mm (2.24 in) W × 180 mm (7.09 in) H × 16 mm (0.63 in) D
Weight	170 Grams

Temp | Humidity | Pressure | Differential Pressure | Vacuum | Gases | Particle | Air Flow
Moisture | Dissolved Oxygen | Radiation | Air Quality | Light / Lux | Distance | Vibration

Instrukart Holdings

Ph : +91 (40)40262020 | Mob : +91 88865 50506;

Email : info@instrukart.com | www.instrukart.com

Head Office: #18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.

 <https://youtube.com/instrukartholdings>

