

HT-306



Features:

- Large Dual Display & Backlight
- Sampling Rate 2.5 sample per second
- Dual Display Temperature & Humidity
- Type K Temperature

Technical Data :

| Function | Range & Resolution | Accuracy |
|----------------------|--------------------|----------------------------|
| Humidity | 5.0 to 98.0% RH | ± 3.5% RH |
| Temperature (K-type) | -20.0 to 199.9°C | ± 3.0% of rdg + 4°C digits |
| | -20 to 1000°C | |
| | -4.0 to 199.9°F | ± 3.0% of rdg + 7°F digits |
| -4 to 1832°F | | |

POWER

9V(6F22) X 1

- Standard Accessories : Carrying case, Manual, TP-01 Temperature Probe
- Dimension : 225(H) x 45(W) x 34(D)mm

HD-304



Features:

- Ambient temperature, Dew point temperature & Wet bulb temperature Fast Response Time
- Large-screen LCD and backlight
- Auto Power OFF (APO)
- 99 groups Data Logging.

Technical Data :

| Basic Functions | Range | Resolution | Accuracy |
|----------------------------|-------------------------------|-------------|---|
| Ambient Temperature | -20 to 60°C (-4 to 140°F) | 0.1 °C / °F | ±0.5°C (0 to 45°C) ±1.0°C(-20 to 0°C, 45 to 60°C) |
| RH | 0 to 100%RH | 0.1% | ±2.0% RH(10% to 90%) ±3.0% RH(0% to 10%,90% to 100%) |
| WB (Wet bulb Temperature) | -20 to 60°C (-4 to 140°F) | 0.1 °C / °F | ±0.5°C (0 to 45°C) ±1.0°C(-20 to 0°C, 45 to 60°C) |
| DP (Dew point Temperature) | -50 to 60°C (-58 to 140°F) | 0.1 °C / °F | ±0.5°C (0 to 45°C) ±1.0°C(-50 to 0°C, 45 to 60°C) |

POWER

AA 1.5V X 4

- Standard Accessories : Hard Carrying Case, Manual
- Dimension : 184 (H) x 60 (W) x 29 (D) MM

Temp | Humidity | Pressure | Differential Pressure | Vacuum | Gases | Particle | Air Flow
Moisture | Dissolved Oxygen | Radiation | Air Quality | Light / Lux | Distance | Vibration

Instrukart Holdings

Ph : +91 (40)40262020 | Mob : +91 88865 50506;

Email : info@instrukart.com | www.instrukart.com

Head Office: #18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.