



FG - 5Kg/FG - 20Kg/FG - 100Kg

Features:

- Dual Display

| MODEL | FG - 5Kg | FG - 20Kg | FG - 100Kg |
|-------------------|--|-----------|------------|
| Force Range | ± 5kgf | ±20kgf | ± 100kgf |
| | ±5000gf | | |
| | ±49N | ±196N | ±980N |
| | ±11Lbf | ±44Lbf | ±220Lbf |
| Resolution | 0.001kgf | 0.01kgf | 0.01kgf |
| | 1gf | | |
| | 0.01N | 0.1N | 0.1N |
| | 0.01Lbf | 0.01Lbf | 0.1Lbf |
| Accuracy | ±0.1%FS ± 1 Digit | | |
| Measurement State | Peak Value Measurement, Real Time Measurement | | |
| Display | 2 Reversed 4 Digit Led | | |
| Power Off | 10 Minutes Auto Power off, Manual Power Off | | |
| Backlight | Blue Backlight | | |
| Safe Load | 150% FS(Buzzer arm Over 110%FS) | | |
| Data Output | USB, Bluetooth (99 Groups) | | |
| Power | AA 1.5V X 2 (UM-3) or 6V DC | | |
| Surrounding | No Vibration Source of Corrosive Medium Around | | |
| Dimension | 211(H)x80(W)x36(D)mm | | |

Temp | Humidity | Pressure | Differential Pressure | Vacuum | Gases | Particle | Air Flow
 Moisture | Dissolved Oxygen | Radiation | Air Quality | Light / Lux | Distance | Vibration

Instrukart

Ph : +91 (40)40262020 | Mob : +91 88865 50506;

Email : info@instrukart.com | www.instrukart.com

Head Office: #18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.