

TECHNICAL DATA

Fluke Networks Pro3000™ Tone Generator and Probe Kit



Key features

- Send tone signal up to 10 miles (16 km) on most cables
- Analog tone generator with bed-of-nails clips, unfiltered probe
- SmartTone™ provides 5 distinct tones for exact pair identification
- Continuity testing and line polarity confirmation
- Ergonomic sleek design, 3.5 mm headphone jack

Product overview: Fluke Networks Pro3000™ Tone Generator and Probe Kit

Pro3000™ analog tone generator and probe kit uses the SmartTone™ technology, with five different tones for exact pair identification, and provides clear and precise tracing of communication cabling. Simply short the selected pair at the near or far end to change the cadence of the tone generated.

Specifications: Fluke Networks Pro3000™ Tone Generator and Probe Kit



Pro3000 Analog Toner Specifications			
User interface		Slide switch selects Continuity or Tone Mode Push button switch selects SOLID, ALT or OFF Tone mode LED Continuity/Polarity LED	
Solid Frequency		1000 Hz nominal	
Alternating Frequency		1000/1500 Hz nominal	
Over Voltage Protection		60 Vdc in Toner/Polarity Mode	
Output Power in Tone Mode		8 dbm into 600 ohms	
Output Voltage Level in Continuity Mode		8 Vdc with fresh battery	
Battery		9V alkaline	
Temperature		Operating: -20° C to 60° C, Storage: -40° C to 70° C	
Case dimensions		2.7 in. x 2.4 in. x 1.4 in. (6.9 cm x 6.1 cm x 3.6 cm)	
Pro3000 Analog Probe Specifications			
User interface	Volume dial Replaceable tip		
Battery	9V alkaline	9V alkaline	
Temperature	Operating: -20° (Operating: -20° C to 60° C, Storage: -40° C to 70° C	
Case dimensions	9.8 in. x 1.6 in. x	9.8 in. x 1.6 in. x 1.3 in. (24.9 cm x 4.1 cm x 3.3 cm)	



Ordering information



26000900

Pro3000™ analog tone generator and probe kit uses the SmartTone™ technology, with five different tones for exact pair identification, and provides clear and precise tracing of communication cabling. Simply short the selected pair at the near or far end to change the cadence of the tone generated.

Includes:

- Pro3000™ Unfiltered Probe
- Pro3000™ Analog Tone Generator

Optional accessories

Description

Fluke Networks Pro3000™ Replacement Tip Replacement tip for Pro3000/3000F series probes.



$\textbf{Fluke}. \ \textit{Keeping your world up and running}. \\ \textcircled{\$}$

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2023 Fluke Corporation.

Specifications subject to change without notice.
11/2023

Modification of this document is not permitted without written permission from Fluke Corporation.