



1+ year battery life



24/7 Monitoring



CFR 21 Complaint



Supports 4 probes



Specifications	Anchor
Dimensions	130mm x 61mm x 25mm
Protection class	IP64
Weight	170gms
Power	USBC 5V, 230V power adapter
Battery	Li-ion, 8700mAh, Rechargeable
Charging Voltage	5V DC, USB Type C
Reading Interval	5 mins (configurable)
Reading Transmission	60 mins (configurable)
Connectivity	WiFi - 2.4GHz, 4G, CAT 1 network
Internal sensor	Temperature: -30°C to +60°C; Accuracy $\pm 0.5^\circ\text{C}$ Humidity: 0 to 100% RH; Accuracy, 3%
External Sensor	External Sensor: -200 to 200; Accuracy $\pm 0.5^\circ\text{C}$ Humidity: 0 to 100% RH; Accuracy, 3%
Probe Sensor	Total Slots available -4 , Sensor type - PT100, interface, USBC.

*Probes are to be procured separately. Device comes with internal sensor only.

Temp | Humidity | Pressure | Differential Pressure | Vacuum | Gases | Particle | Air Flow
Moisture | Dissolved Oxygen | Radiation | Air Quality | Light / Lux | Distance | Vibration

Instrupreneurs Pvt Ltd. India

Ph: +91 (40)40262020 | Mob : +91 88977 87780;
Email : techsupport@instrukart.com | www.instrukart.com

Head Office: #18, Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.

